

CRB 25W-50

Longer engine life for diesel engines

Description

Castrol CRB 25W-50 diesel engine oil is designed to provide excellent protection, especially at high engine temperatures, ensuring longer engine life. It is designed for naturally aspirated diesel engine vehicles and is also suitable for use in tractors and agricultural equipment.

Advantages

Castrol CRB 25W-50 with Heat Proof Formula forms a protective layer that works harder at high engine temperature, ensuring longer engine life.

User benefits include:

- Greater protection against wear even at high temperature conditions
- Maintains excellent oil pressure in older engines
- Reduced oil consumption

Typical Characteristics

Name	Method	Units	CRB 25W-50
Density @ 15C	ASTM D4052	g/ml	0.897
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	17.9
Viscosity, CCS -10C (25W)	ASTM D5293	mPa.s (cP)	7500
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	183
Viscosity Index	ASTM D2270	None	107
Ash, Sulphated	ASTM D874	% wt	0.9
Total Base Number, TBN	ASTM D2896	mg KOH/g	7.8
Pour Point	ASTM D97	°C	-36
Flash Point, PMCC	ASTM D93	°C	222

Product Performance Claims

API CF-4

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

CRB 25W-50

04 Aug 2023

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Castrol Lubricants (Malaysia) Sdn. Bhd., Registration No. 198701007157 (165875-W), Level 9, Tower 5, Avenue 7, The Horizon Bangsar South City No.8,
Jalan Kerinchi, 59200 Kuala Lumpur
Phone No : 03-22818181 Toll free Line: 1-800-81-6530
www.castrol.com