SAFETY DATA SHEET



Section 1. Identification			
Product name	Hyspin VG 32		
SDS #	453036		
Historic SDS #:	12100		
Code	453036-US03		
Relevant identified uses of t	he substance or mixture and uses advised against		
Product use	Hydraulic fluid. For specific application advice see appropriate Technical Data Sheet or consult our company representative.		
Supplier	BP Lubricants USA Inc. 1500 Valley Road Wayne, NJ 07470 Telephone: +1-888-CASTROL Product Information: +1-877-641-1600		
EMERGENCY HEALTH INFORMATION:	+1-800-447-8735		
EMERGENCY SPILL INFORMATION:	+1-800-424-9300 (CHEMTREC USA) +1-703-527-3887 (CHEMTREC outside the US)		

Section 2. Hazards identification

OSHA/HCS status	This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).		
Classification of the substance or mixture	Not classified.		
GHS label elements			
Signal word	No signal word.		
Hazard statements	No known significant effects or critical hazards.		
Precautionary statements			
Prevention	Not applicable.		
Response	Not applicable.		
Storage	Not applicable.		
Disposal	Not applicable.		
Hazards not otherwise classified	Defatting to the skin. Note: High Pressure Applications Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data Sheet.		

Section 3. Composition/information on ingredients

Mixture

Substance/mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Ingredient name	CAS number	%
	64742-54-7 64742-54-7	≥50 - ≤75 ≥25 - ≤50

Product name	Hyspin VG 32		Product code	453036-US03	Page: 1/9
Version 5.01 D	ate of issue 07/09/2020.	Format	US	Language	ENGLISH

Section 3. Composition/information on ingredients

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.
Skin contact	Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate m	edical attention and special treatment needed, if necessary
Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects.
	Note: High Pressure Applications Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discolored and extremely painful with extensive subcutaneous necrosis. Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimize tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances along tissue planes.
Specific treatments	No specific treatment.

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet.
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	None expected.
Special protective actions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.
Special protective equipment for fire-fighters	Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective	e equipment and emergency procedures		
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.		
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non- emergency personnel".		
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).		
Methods and materials for cont	ainment and cleaning up		
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.		
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.		

Section 7. Handling and storage

Precautions for safe handling			
Protective measures	Put on appropriate personal protective equipment (see Section 8).		
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.		
Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.		

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Distillates (petroleum), hydrotreated heavy paraffinic

ACGIH TLV (United States).

TWA: 5 mg/m³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction **OSHA PEL (United States).** TWA: 5 mg/m³ 8 hours. Issued/Revised: 6/1993

Distillates (petroleum), hydrotreated heavy paraffinic

ACGIH TLV (United States).

TWA: 5 mg/m³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction **OSHA PEL (United States).** TWA: 5 mg/m³ 8 hours. Issued/Revised: 6/1993

Product code 4

Section 8. Exposure controls/personal protection

Appropriate engineering controls	All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	Safety glasses with side shields.
Skin protection	
Hand protection	Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.
Body protection	Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

Version 5.01 Date of is	<mark>ssue</mark> 07/09/2020.	Format US	Langua	ge ENGLISH
Product name Hyspin	VG 32	Product code	453036-US03	Page: 4/9
Melting point	Not available.			
рН	Not available.			
Odor threshold	Not available.			
Odor	Not available.			
Color	Yellow. [Light]			
Physical state	Liquid.			
<u>Appearance</u>				

Section 9. Physical and chemical properties

Boiling point	Not available.
Flash point	Closed cup: >160°C (>320°F) [Pensky-Martens.] Open cup: 210°C (410°F) [Cleveland.]
Pour point	-30 °C
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable. Based on - Physical state
Lower and upper explosive (flammable) limits	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Density	<1000 kg/m³ (<1 g/cm³) at 15.6°C
Solubility	insoluble in water.
Partition coefficient: n- octanol/water	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Kinematic: 32 mm²/s (32 cSt) at 40°C

Section 10. Stability and reactivity

Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials.
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects				
Aspiration hazard				
Name Result				
Distillates (petroleum), hydro	treated heavy paraffinic	ASPIRATION HAZARD - Category 1		
Information on the likely routes of exposure	Routes of entry anticipated: De	rmal, Inhalation.		
Potential acute health effects	<u>S</u>			
Eye contact	No known significant effects or	critical hazards.		
Skin contact	No known significant effects or critical hazards.			
Inhalation	Vapor inhalation under ambient conditions is not normally a problem due to low vapor pressure.			
Ingestion	No known significant effects or	critical hazards.		
Symptoms related to the physical, chemical and toxicological characteristics				
Eye contact	No specific data.			

Product name Hyspin VG 32	Product code	453036-US03 Page: 5/9
Version 5.01 Date of issue 07/09/2020.	Format US	Language ENGLISH

Section 11. Toxicological information

Skin contact	Adverse symptoms may include the following: irritation drvness
	cracking
Inhalation	No specific data.
Ingestion	No specific data.
Delayed and immediate effects	and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	Not available.
Potential delayed effects	Not available.
Long term exposure	
Potential immediate effects	Not available.
Potential delayed effects	Not available.
Potential chronic health effect	<u>s</u>
General	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates Not available.

Section 12. Ecological information

Toxicity

No testing has been performed by the manufacturer.

Persistence and degradability

Not expected to be rapidly degradable.

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

<u>Mobility in soil</u>	
Soil/water partition coefficient (Koc)	Not available.
Mobility	Spillages may penetrate the soil causing ground water contamination.
Other adverse effects	No known significant effects or critical hazards.
Other ecological information	Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Product name Hyspin VG 32	Product code	453036-US03	Page: 6/9
Version 5.01 Date of issue 07/09/2020.	Format US	Languaç	ge ENGLISH

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

Special precautions for user Not available.

Transport in bulk according Not available. to Annex II of MARPOL and the IBC Code

Section 15. Regulatory information

U.S. Federal regulations United States inventory

All components are active or exempted.

(TSCA 8b) SARA 302/304

Composition/information on ingredients

No products were found.

SARA 311/312	
Classification	Not applicable.
<u>SARA 313</u>	
Form R - Reporting requirements	This product does not contain any hazardous ingredients at or above regulated thresholds.
Supplier notification	This product does not contain any hazardous ingredients at or above regulated thresholds.
State regulations	
Massachusetts	The following components are listed: OIL MIST, MINERAL; OIL MIST, MINERAL
New Jersey	None of the components are listed.
Pennsylvania	None of the components are listed.

Product name Hyspin VG 32	Product code	453036-US03	Page: 7/9
Version 5.01 Date of issue 07/09/2020.	Format US	Language	ENGLISH

Section 15. Regulatory information

California Prop. 65

MARNING: This product can expose you to chemicals including Ethyl acrylate, Ethyl acrylate, Naphthalene, 1-Naphthylamine, 2-Naphthylamine and Aniline, which are known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Other regulations	
Australia inventory (AICS)	All components are listed or exempted.
Canada inventory	All components are listed or exempted.
China inventory (IECSC)	All components are listed or exempted.
Japan inventory (ENCS)	All components are listed or exempted.
Korea inventory (KECI)	All components are listed or exempted.
Philippines inventory (PICCS)	All components are listed or exempted.
Taiwan Chemical Substances Inventory (TCSI)	All components are listed or exempted.

REACH Status

For the REACH status of this product please consult your company contact, as identified in Section 1.

Section 16. Other information

National Fire Protection Association (U.S.A.)



History

Date of issue/Date of 07/09/2020. revision	
Date of previous issue 07/23/2019.	
Prepared by Product Stewardship	
GHS = Globally Harmonized S IATA = International Air Trans IBC = International Maritime LogPow = logarithm of the oct MARPOL = International Conv modified by the Protocol of 19 OEL = Occupational Exposure SDS = Safety Data Sheet STEL = Short term exposure li TWA = Time weighted average UN = United Nations UN Number = United Nations Nations Committee of Experts Varies = may contain one or m 64741-96-4, 64742-01-4, 6474	r tracts Service Registry Number system of Classification and Labelling of Chemicals bort Association ainer Dangerous Goods anol/water partition coefficient rention for the Prevention of Pollution From Ships, 1973 as 78. ("Marpol" = marine pollution) • Limit mit e Number, a four digit number assigned by the United on the Transport of Dangerous Goods. hore of the following 64741-88-4, 64741-89-5, 64741-95-3, 12-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 12-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0,

V Indicates information that has changed from previously issued version.

Notice to reader

Product name Hyspin VG 32	Product code	453036-US03	Page: 8/9
Version 5.01 Date of issue 07/09/2020.	Format US	Language	e ENGLISH

Section 16. Other information

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.