SAFETY DATA SHEET



Optileb GT 320

Section 1. Identification

GHS product identifier Optileb GT 320
Product code 450718-DE54
SDS no. 450718

Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/ Gear lubricant

mixture For specific application advice see appropriate Technical Data Sheet or consult our

company representative.

Manufacturer

Supplier BP Southern Africa (Pty)Ltd

199 Oxford Road Oxford Parks Dunkeld, 2196 South Africa

Product Technical Helpdesk: 0800 111 551

EMERGENCY TELEPHONE NUMBER

Tygerberg Poison Centre: 0861 555 777 Carechem: +27 21 300 2732 (24/7)

Section 2. Hazards identification

GHS Classification SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 3

LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 3

GHS label elements

Signal word No signal word.

Hazard statements H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention P273 - Avoid release to the environment.

Response Not applicable.
Storage Not applicable.

Disposal P501 - Dispose of contents and container in accordance with all local, regional,

national and international regulations.

Other hazards which do not result in classification

Defatting to the skin.

Section 3. Composition/information on ingredients

Substance/mixture Mixture

Synthetic lubricant and additives.

Ingredient name	%	CAS number
2,6-ditert-butyl-p-cresol (Z)-N-methyl-N-(1-oxo-9-octadecenyl)glycine	≤1 ≤0.3	128-37-0 110-25-8

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Product name Optileb GT 320Product code450718-DE54Page: 1/7Version 1Date of issue 18/10/2021.Format GHS - South AfricaLanguage ENGLISHBuild 6.1.0(GHS - Default)(ENGLISH)

Section 4. First aid measures

Description of necessary first aid measures

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eye contact

Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for

and remove any contact lenses. Get medical attention.

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Wash skin thoroughly with soap and water or use recognised skin cleanser. Skin contact

Remove contaminated clothing and shoes. Wash clothing before reuse. Clean

shoes thoroughly before reuse. Get medical attention if symptoms occur.

Ingestion Do not induce vomiting unless directed to do so by medical personnel. Never give

anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Get medical attention if adverse

health effects persist or are severe.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Specific treatments No specific treatment.

Notes to physician Treatment should in general be symptomatic and directed to relieving any effects.

Section 5. Firefighting measures

Extinguishing media

Suitable Use foam or all-purpose dry chemical to extinguish.

Not suitable Do not use water jet.

Specific hazards arising from the chemical

Swarf fires - Neat metal working oils may fume, thermally decompose or ignite if they come into contact with red hot swarf. To minimise the generation of red hot swarf ensure that a sufficient flow of oil is correctly directed to the cutting edge of the tool to flood it throughout cutting operations. As an additional precaution swarf should be regularly cleared from the immediate area to prevent the risk of fire. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects.

Hazardous thermal decomposition products Combustion products may include the following:

Special precautions for fire-

carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if

there is a fire.

Special protective equipment for fire-fighters Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

For emergency responders

Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Product name Optileb GT 320 Product code 450718-DF54 Page: 2/7 Language ENGLISH Date of issue 18/10/2021. Format GHS - South Africa Version 1 (ENGLISH)

Build 6.1.0 (GHS - Default)

Section 6. Accidental release measures

Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Contaminated absorbent material may pose the same hazard as the spilt product. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid contact of spilt material and runoff with soil and surface waterways. Concentrations of mist, fumes and vapours in enclosed spaces may result in the formation of explosive atmospheres. Excessive splashing, agitation or heating must be avoided. During metal working, solid particles from workpieces or tools will contaminate the fluid and may cause abrasions of the skin. Where such abrasions result in a penetration of the skin, first aid treatment should be applied as soon as reasonably possible. The presence of certain metals in the workpiece or tool, such as chromium, cobalt and nickel, can contaminate the metalworking fluid, as can bacteria, and as a result may induce allergic and other skin reactions, especially if personal hygiene is inadequate.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Recommended monitoring procedures

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Product name Optileb GT 320

Version 1

Product code 450718-DE54

Page: 3/7

Date of issue 18/10/2021.

Format GHS - South Africa

Language ENGLISH

Build 6.1.0

(GHS - Default)

(ENGLISH)

Section 8. Exposure controls/personal protection

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye protection Skin protection

Safety glasses with side shields.

Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Skin protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. For protection against metal working fluids, respiratory protection that is classified as "resistant to oil" (class R) or oil proof (class P) should be selected where appropriate. Depending on the level of airborne contaminants, an air-purifying, half-mask respirator (with HEPA filter) including disposable (P- or R-series) (for oil mists less than 50mg/m3), or any powered, air-purifying respirator equipped with hood or helmet and HEPA filter (for oil mists less than 125 mg/m3).

Where organic vapours are a potential hazard during metalworking operations, a

combination particulate and organic vapour filter may be necessary.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

Appearance

Physical state Liquid.

Colour Yellow. [Light] Odour Not available. Not available. **Odour threshold** pН Not applicable. **Melting point** Not available. **Boiling point** Not available. Pour point -45 °C **Drop Point** Not available.

Flash point Open cup: 234°C (453.2°F) [Cleveland.]

Evaporation rate Not available.

Product name Optileb GT 320
Product code 450718-DE54
Page: 4/7

Version 1
Date of issue 18/10/2021.
Format GHS - South Africa
Language ENGLISH

Build 6.1.0 (GHS - Default) (ENGLISH)

Section 9. Physical and chemical properties

Flammability (solid, gas) Not applicable. Based on - Physical state

Lower and upper explosive

(flammable) limits

Not available.

Vapour pressure Not available. Vapour density Not available. Relative density Not available.

<1000 kg/m3 (<1 g/cm3) at 15°C **Density**

Solubility insoluble in water. Partition coefficient: n-Not available.

octanol/water

Auto-ignition temperature Not available. **Decomposition temperature** Not available.

Viscosity Kinematic: 314.8 mm²/s (314.8 cSt) at 40°C Kinematic: 36.2 mm²/s (36.2 cSt) at 100°C

Section 10. Stability and reactivity

No specific test data available for this product. Refer to Conditions to avoid and Reactivity

Incompatible materials for additional information.

Chemical stability The product is stable.

Possibility of hazardous Under normal conditions of storage and use, hazardous reactions will not occur. reactions

Under normal conditions of storage and use, hazardous polymerisation will not occur.

Conditions to avoid Avoid excessive heat.

Incompatible materials Reactive or incompatible with the following materials: oxidising materials.

Hazardous decomposition Under normal conditions of storage and use, hazardous decomposition products

should not be produced. products

Section 11. Toxicological information

Information on toxicological effects

Aspiration hazard

Not available.

Information on likely routes

of exposure

Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Eye contact No known significant effects or critical hazards.

Inhalation Vapour inhalation under ambient conditions is not normally a problem due to low

vapour pressure.

Skin contact Defatting to the skin. May cause skin dryness and irritation.

Ingestion No known significant effects or critical hazards. Symptoms related to the physical, chemical and toxicological characteristics

Eye contact No specific data. Inhalation No specific data.

Skin contact Adverse symptoms may include the following:

irritation dryness cracking

Ingestion No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Eye contact Potential risk of transient stinging or redness if accidental eye contact occurs. Inhalation Overexposure to the inhalation of airborne droplets or aerosols may cause irritation

of the respiratory tract.

Skin contact Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/

or dermatitis.

Ingestion Ingestion of large quantities may cause nausea and diarrhoea.

Potential chronic health effects

General No known significant effects or critical hazards. Carcinogenicity No known significant effects or critical hazards.

450718-DE54 Product name Optileb GT 320 Product code Page: 5/7 Language ENGLISH Version 1 Date of issue 18/10/2021. Format GHS - South Africa

> (ENGLISH) Build 6.1.0 (GHS - Default)

Section 11. Toxicological information

MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

Section 12. Ecological information

Environmental effects

This material is harmful to aquatic life with long lasting effects.

Persistence and degradability

Not expected to be rapidly degradable.

Bioaccumulative potential

Not available.

Mobility Liquid. insoluble in water.

Other adverse effects No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	IMDG	IATA
UN number	Not regulated.	Not regulated.
UN proper shipping name	-	-
Transport hazard class(es)	-	-
Packing group	-	-
Environmental hazards	No.	No.
Additional information	-	-

Special precautions for user Not available.

Transport in bulk according

Not available.

to IMO instruments

Section 15. Regulatory information

Regulation according to other foreign laws

REACH StatusThe company, as identified in Section 1, sells this product in the EU in compliance with the

current requirements of REACH.

Australia inventory (AICS)

Canada inventory status

China inventory (IECSC)

All components are listed or exempted.

All components are listed or exempted.

All components are listed or exempted.

Product name Optileb GT 320

Product code 450718-DE54

Page: 6/7

Version 1

Date of issue 18/10/2021.

Format GHS - South Africa

Language ENGLISH

Build 6.1.0 (GHS - Default) (ENGLISH)

Section 15. Regulatory information

Japan inventory (ENCS)

Korea inventory (KECI)

Philippines inventory

All components are listed or exempted.

All components are listed or exempted.

At least one component is not listed.

(PICCS)
Taiwan Chemical

Substances Inventory (TCSI)

All components are listed or exempted.

United States inventory (TSCA 8b)

All components are active or exempted.

South Africa

National regulations National legislation: Occupational Health and Safety Act (Act 85 of 1993).

Section 16. Other information

History

Date of issue/Date of 18/10/2021.

revision

Date of previous issueNo previous validation.Prepared byProduct Stewardship

Key to abbreviations ACGIH = American Conference of Industrial Hygienists

CAS Number = Chemical Abstracts Service Registry Number

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association IMDG = International Maritime Dangerous Goods

OEL = Occupational Exposure Limit

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

Regulation [Regulation (EC) No. 1907/2006]

SDS = Safety Data Sheet STEL = Short term exposure limit TWA = Time weighted average

UN Number = United Nations Number, a four digit number assigned by the United

Nations Committee of Experts on the Transport of Dangerous Goods. Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

72623-87-1

▼ Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Optileb GT 320Product code450718-DE54Page: 7/7Version 1Date of issue 18/10/2021.Format GHS - South AfricaLanguage ENGLISH

Build 6.1.0 (GHS - Default) (ENGLISH)